














Pos.			Contact-complement	Drawing No.	Type	Weight gramm	Price EURO
1		Knob solid 42 mm Ø		KBAD 66	GK1	35	
2		Knob 42 mm Ø with push button top	1 change over contact 0,5 A 250 V AC 15 1,5 A 24 V DC 13	KHS/177	GK2	25	
3		Knob 42 mm Ø with push button operated by twisting the upper knob half	1 change over contact 0,5 A 250 V AC 15 1,5 A 24 V DC 13	KBAD/230	GK3	170	
4		Knob solid 25 mm Ø with M 6		KBAD 271	GK4	10	
5		Knob solid 27 mm Ø with M 8		KBAD 302	GK5	15	
6		Knob solid 29 mm Ø		KBAD/141	GS6	70	
7		Knob 29 mm Ø with push button top	1 change over contact 0,5 A 250 V AC 15 1,5 A 24 V DC 13	KBAD/210	GS7	60	
8		T-grip solid 28 mm Ø x 58 mm		KBAD 148	Q8	50	
9		T-grip 28 mm Ø x 58 mm with push button side	1 change over contact 0,5 A 250 V AC 15 1,5 A 24 V DC 13	KBAD 147	Q9	60	
10		T-grip solid 28 mm Ø x 80 mm		KBAD 355	Q10	50	
11		T-grip 28 mm Ø x 98 mm with push button side	1 change over contact 0,5 A 250 V AC 15 1,5 A 24 V DC 13	KBAD 329	Q11	60	
12							
21		Cable 4 x 0,25 mm <sup>2</sup> x 450 mm long, wired included Pos. 1-12 Additional price per metre cable 4-pole					



Type → operator handles

switch devices ↓

	GK 1	GK2	GK3	GK4	GK5	GS6	GS7	Q8	Q9	Q10	Q11	B1	B2	B3		B5
V 6	X		X					X	X			X		X		X
V V6	X		X					X	X			X		X		X
V 11	X		X					X	X			X				X
V 5	X							X				X				X
VV 5	X		X					X	X			X		X		X
V 8	X	X	X					X	X			X	X	X		X
VV 8	X	X	X					X	X			X	X	X		X
V 10	X				X	X	X									X
V 14				X		X										
V 3	X							X				X				X
D/ DD64	X							X	X							
D 8	X							X	X							
D 3	X									X	X					
S 2	X		X			X	X	X	X			X				X
S 21	X		X			X	X	X	X			X				X
S 22	X		X			X	X	X	X			X				X
SS 22	X		X			X	X	X	X			X				X
S 23	X									X						
S 3	X									X	X					
S 14				X		X										
S 6	X	X	X					X	X			X				X