



The palm grip B 5 is an actuating element for our multi-axis and single axis controller. It can also be used as an actuating element for hydraulic drives. Pushbuttons, rocker switches, e.t.c., can also be fitted to suit appropriate requirements.

The palm grip has a highly flexible cable 4 (8) x 0,25 mm<sup>2</sup> x 450 mm long.

The mounting piece for the drive rod can be supplied with a tapped hole M 8 or M 10 (standard = M 10).

The palm grip B 5 is made of Noryl plastic and is black in color.

**Contact complement**      2 A 250 V AC 15 / 3 A 24 V DC 13  
or                                    0,5 A 250 V AC 15 / 1,5 A 24 V DC 13

Permissible ambient temperature      Operating      -40°C to +60°C  
Storage                                        -50°C to +80°C

Climate resistance  
Damp heat constant                        DIN IEC 68 part 2-3  
Damp heat cyclic                            DIN IEC 68 part 2-30  
Degree of protection front                IP 54 IEC 529 DIN 40050

Pos.				Contact-complement	Drawing No.	Type	Weight gramm	Price EURO
1		without built in			KBAD / 254	B 5	100	
2		Rocker switch top tast-0-tast	T - O - T	2 change over contacts 2A 250V AC 15	KBAD / 248	B 5 W	120	
3		Rocker switch top tast-0-rest	T - O - R					
4		Rocker switch top rest-0-rest	R - O - R					
5		Rocker switch top tast-0-tast with push button side	T - O - T	2 change over contacts 2A 250V AC 15 1 change over contact 0,5A 250V AC 15	KBAD / 294	B 5 WD	130	
7		push button top mechanical operation		1 change over contact 0,5A 250V AC 15	KBAD / 292 KBAD / 250	B 5 T B 5 D	120 100	
8		push button top						
9		push button top with 1 push button side		2 change over contacts 0,5A 250V AC 15	KBAD / 252	B 5 DD	120	
11		1 push button side		change over contact 0,5A 250V AC 15	KBAD / 246	B 5 D B 5 DD	110 120	
12		2 push button side						
21		Cable 4 res. 8 x 0,25 mm <sup>2</sup> x 450 mm lang wired included in Pos. 1-12						
22		Additional price per metre cable 4-pole Additional price per metre cable 8-pole						