



driver's seat KFS 2 as shown

The crane control unit KST 75 combines in its design the crane driver's seat and the control and monitoring devices. Ready wired, it can be easily and quickly installed in the crane cabin.

Equipment boxes: Sheet steel.

The equipment boxes with the devices fitted have hinged tops that can be locked in position. They contain the termination and connection facilities and a lockable plug-in cover on the inside.

Seat KFS 2: The seat backrest can be tipped forwards and further tipped together with the cushion. The cushion and seat backrest are padded.

Adjusting possibilities: Cushion horizontally and vertically. Height adjustment via a gas-loaded spring in the seat base. Seat backrest horizontally and vertically to the cushion. Arm rests and adjustable in height. Fixed to the equipment boxes.

Surface treatment: Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 7032 pebble-gray. All non-painted metal parts are electrogalvanized and chromed.

Description data look catalog 5/003/004

Permissible ambient temperature	Operation -40° C to + 60° C Storage -50° C to + 80° C
Climate resistance	
Damp heat constant	DIN IEC 68 part 2-3
Damp heat cyclic	DIN IEC 68 part 2-30
Degree of protection	IP 54 IEC 529 DIN 40050

Pos.		Type	Weight kg	Price EURO
1	Crane control unit with driver's seat	KFS 2 with base plate	KST 75 51	
2	Crane control unit with driver's seat	KFS 2 without base plate	KST 76 46	
3	Crane control unit without driver's seat	KFS 2 with base plate	KST 77 36	
4	Crane control unit without driver's seat	KFS 2 without base plate	KST 78 31	
5				
10	Driver's seat	look catalog 2/130 (picture shows)	KFS 2	
11	Driver's seat	look catalog 2/131	KFS 3	
12	Driver's seat	look catalog 2/132	KFS 4	
13				
14				
15	Driver's seat	look catalog 2/140	KFS 9	
20	Multi-axis controller	look catalog 1/100		
21	Single-axis controller	look catalog 1/200		
22	Double-handle	look catalog 1/160		
23	Control-switch	look catalog 1/220		
24	Command and indicating devices	look catalog 1/360		
25				
30	Terminal block 4 mm ² without wiring each terminal	KL		
31	Terminal block 4 mm ² with wiring wire 1,5 mm ² each terminal	KL		
32	External wiring single wire highly flexible 1,5 mm ² x 5 metre long			
33	Additional or subtract price each metre			
34				
35				
40	Special painted			
41	Indicating labels not engraved with 2 or 4 arrows			
42	Engraved each 10 characters			
43				

